



# EU Declaration Of Conformity (DoC)

Document No.  
13001029EU  
Rev. 00

We, the undersigned,

Company Name :	<b>Giovenzana International B.V.</b>
Address :	Strawinskylaan 1105 - 1077 XX AMSTERDAM (NL)
Phone :	Ph. +31(0)20.4413576 - Fax +31(0)20.4413456
E-mail :	<a href="mailto:giovenzana@giovenzana.com">giovenzana@giovenzana.com</a>
Web :	<a href="http://www.giovenzana.com">www.giovenzana.com</a>

Declare that the DoC is issued under our sole responsibility and belongs to the following product:

Product Description:	<b>LINE 30 AND LINE 41 SYSTEM</b>
Model(s):	30 - 41

### **SPECIFIC CONDITIONS OF USE: YES as shown below:**

Ambient temperature range:  $-25^{\circ}\text{C} \leq T_{\text{amb}} \leq +80^{\circ}\text{C}$ .

Only rail system supplied by GIOVENZANA International B.V. shall be used.

The minimum distance between the floor and the towing trolley shall be 3 m.

Do not paint or cover with non-conductive layers any equipment composing the trolley system.

### **PARAMETERS RELATING TO THE SAFETY**

The maximum speeds admitted and maximum loads admitted for each trolley are reported in the following table:

Type of trolley:	Series 30		Series 41	
	Max Load	Max Speed	Max Load	Max Speed
Non-metallic Trolley	15 Kg	0.83 m/s (50 m/min)	20 Kg	0.83 m/s (50 m/min)
Metallic Trolley	30 Kg	0.9 m/s (54 m/min)	35 Kg	0.9 m/s (54 m/min)

C-rail bar: Max. Length 4m

Bracket: Max. Length 0.8m

Maximum distance allowed between 2 supports of Track support bracket or Support arm bracket or Track support bracket for ceiling: 1 m

Signature - Manufacturer

Massimo Giovenzana  
(President)

Place

Amsterdam

Date

03/12/2021